

Zirkon® Gas Cl₂

Kuntze Gas sensors are amperometric sensors for the detection of chlorine dioxide gas. The matching fitting Ne GSH allows for an easy installation of the gas sensor.

Advantages

- > Short response times
- > High reliability
- > Simple start-up due to printed calibration value

Zirkon® Gas Cl₂



Article No.: S29111001K

Measurement Parameter

- > Chlorine: 0.. 20 ppm*
- *Range of measurement device can deviate.

Process Conditions

- > Response Time (T₉₀): < 60 s
- > Temperature: -20.. +40 °C / -4..104 °F
- > Humidity: 15.. 90 % rH (non condensating)
- > Storage Life: 6 months in container at 4..10 °C / 39.2..50 °F
- > Influence of Humidity: No effect on the zero point
- > Air Pressure: 800-1200 hPa

Cross Sensitivity Chlorine Dioxide sensor at 20 °C / 68 °F

| Gas | Concentration | Value Read |
|---------------------------------------|---------------|------------|
| Carbon Monoxide | 100 ppm | 0 ppm |
| Hydrogen | 3000 ppm | 0 ppm |
| Hydrogen Sulfide (H ₂ S) * | 20 ppm | ND |
| Isopropanol | 600 ppm | 0 ppm |
| Chlorine | 1 ppm | 2 ppm |
| Ozone | 0.25 ppm | 0.3 ppm |

* Contact with H₂S poisons the sensor, subsequent contact with chlorine dioxide reactivates it.

The influencing factor can vary from sensor to sensor and over the life span of the individual sensor. No claim to completeness of the data, the sensors can potentially exhibit cross sensitivity to other gases.