



Handheld pH/conductivity Meter

Feature:

2. Large LCD display 21 x 18 mm for reading convenient.
3. Impact resistant ABS case by waterproof designed IP 57 rated.
4. 1 or 2 points(pH only) manual calibration via screw trim pot.
5. The electrode module are changeable for replacement by user.

Specifications:



| | 6011 | 6011A | 6021 | 6022 | 6031 | 6032 | 6041 | 6061 |
|------------|-------------------------------|---------------|--------------|--------------|-------------|------------|----------|------------|
| Type | pH | pH | Conductivity | Conductivity | TDS | TDS | ORP | EC |
| Range | 0~14.0 | 0~14.00 | 0~19990 uS | 0~1999 uS | 0~19990 ppm | 0~1999 ppm | ±1999 mV | 0~19.99 EC |
| Accuracy | ±0.1+1 digit | ±0.01+1 digit | ± 1% FS | ± 1% FS | ± 1% FS | ± 1% FS | ± 2% FS | ± 1% FS |
| Resolution | 0.1 pH | 0.01 pH | 10 uS/cm | 1 uS/cm | 10 ppm | 1 ppm | 1 mV | 0.01 EC |
| ATC | No | Yes | Yes | Yes | Yes | Yes | N/A | Yes |
| Power | 3V x 2 Lithium battery CR2032 | | | | | | | |
| Dimension | Meter: 33.5 x 170 mm | | | | | | | |
| Weight | Meter: 85 g(w/battery) | | | | | | | |

Accessories for complete kit:

1. Standard solution
2. Battery
3. Screwdriver
4. Gift box

