

א.ב. מולי סחר ושרותים בע"מ

A.B. Moli Trade & Services Ltd.



Industrial Online digital pH meter PH-5520

Product Information

Online ph meter / pH controller PH-5520 ('pH meter') is an industrial online ph analysis and ph monitoring instrument. The online ph meter /ph tester is with various software functions, and has such features as easy installation and operation, strong anti-interference capability and little amount of maintenance work. High-accuracy temperature compensation and pH operation compensation is also adopted for this ph meter.

The online ph meter /ph tester is Widely used for online pH monitoring in environmental protection water treatment, pure water treatment, industrial process, agricultural industry etc.

Technical specifications



Model	5500	5510	5520
Power supply	DC24V	AC110	AC220V
Supply frequency	-----	50/60	50/60
Measurement range	pH	0.00~ 14.00	
	ORP	-1000mV~ +1000mV	
	Temp.	0.0 ~99.9°C	
Resolution	pH	0.01	
	ORP	1mV	
	Temp	0.1°C	
Indication error	pH	$\leq\pm 0.05$	
	ORP	$\leq\pm 5$ mV	
	Temp	$\leq \pm 0.5^\circ C$	
Input impedance cause value error	pH	± 0.03	
Approx equivalent input impedance		$5\times 10^{12}\Omega$	
PH buffer solution		10.0;9.18;7.00;6.86;4.00; 4.01	
Temp. compensation error	pH	$\leq\pm 0.05$	

POB 1397, KFAR-SABA 44113, ISRAEL

fax 972 9 7440681

[HTTP://WWW.ABMOLI.COM](http://WWW.ABMOLI.COM)

ת.ד. 1397, כפר-סבא 44113

TEL 972 9 7434264

דוא"ל E-mail info@abmoli.com

א.ב. מולי סחר ושרותים בע"מ

A.B. Moli Trade & Services Ltd.



Entire instrument error	pH	$\leq \pm 0.1$
Entire instrument repeatability error	pH	0.05
	ORP	$\pm 2\text{mV}$
Compensation range	Temp.	0 ~ 50°C
Working environment	Temp.	0 ~ 50°C
	Humidity	$\leq 85\% \text{ RH}$
Cable length		$\leq 20\text{m}(\text{standard } 10\text{m})$
Control output		double relay(single contact ON/OFF), hysteresis can be set
Contact capacity		3A(max), AC220V/AC110V 3A(max), DC24V
Power consumption		<2.5W
(4~20)mA current loop	Channels	One channel
	Technical features	Isolated, transferable, adjustable, instrument/transmitter mode
	Loop	$\leq 500\Omega(\text{max}), \text{DC}24\text{V}$
	Accuracy	$\pm 0.1\text{mA}$
Protection grade level		IP65(with rear cover)
Installation		Panel mounted, fast installation clamp
Dimension		96 mm×96mm×103 mm (H×W×D)
hole dimension		91mm×91mm

POB 1397, KFAR-SABA 44113, ISRAEL
פקס 972 9 7440681
[HTTP://WWW.ABMOLI.COM](http://WWW.ABMOLI.COM)

ת.ד. 1397, כפר-סבא 44113
טל. 972 9 7434264
דוא"ל E-mail info@abmoli.com